


ELEVATING ARTISTRY




**DECOR**  
COLLECTION



**800x1600mm**

9mm Thickness



## Décor Story

The Décor Collection offers an array of design options to cater to various aesthetics and preferences. From classic patterns that exude timeless charm to contemporary designs that embrace modern sensibilities, these tiles are versatile and adaptable to a wide range of interior styles.

With their impressive size and high-quality finish, these tiles effortlessly enhance the visual appeal of any room, making them a perfect choice for creating feature walls, backsplashes, or flooring that demands attention. Elevate your space with the Décor Collection, where every tile is a masterpiece in its own right, and every room becomes a work of art.



800  
x1600mm





Feel the creative freedom of impressive formats

## Product Features

Décor tiles are the ideal choice for flooring as it's tough and does not easily deteriorate. As well as Décor tile is also more comfortable to walk on because of its modest softness to the touch.

9MM Thickness	Frost Resistance	High Load Resistance	Thermal Impact	Anti-slip Finish

Removable & Reuse	Easy to Install	Chemical Resistance	Ecological Finish	Fire Proof

## Application Areas



Décor tile can be an extremely resilient floor covering that endures high-traffic areas with an adequate finish. Décor tile is first-rate, with unrivaled quality and appeal. These tiles are for use, among several other locations, in bedrooms and living rooms.




800x  
1600mm

Glossy  
Finish

9mm  
Thickness




Passion Grey



Passion Grey Décor - 1



Endless - 4 Faces






800x  
1600mm

Glossy  
Finish


9mm  
Thickness




Passion Grey



Passion Grey Décor - 2



Endless - 4 Faces






800x  
1600mm

Glossy  
Finish

9mm  
Thickness




Swiss Onyx



Swiss Onyx Décor



Endless - 4 Faces







800x  
1600mm

Glossy  
Finish

9mm  
Thickness




Statuario Regal



Statuario Regal Décor - 1



Random - 5 Faces







800x  
1600mm

Glossy  
Finish


9mm  
Thickness




Statuario Regal



Statuario Regal Décor - 2



Random - 5 Faces





800x  
1600mm

Glossy  
Finish

9mm  
Thickness



**Domino Crema**



**Domino Crema Décor**



**Endless - 4 Faces**







800x  
1600mm

Glossy  
Finish


9mm  
Thickness




Carnico Grey



Carnico Grey Décor



Random - 4 Faces





800x  
1600mm

Glossy  
Finish


9mm  
Thickness




Calacatta Bronzo



Carnico Grey Décor




Random - 4 Faces







## WORKING WITH THE VARIOUS VERSIONS OF TILES FINISH

### CUTTING WITH DIAMOND DISCS



Our products can be cut using diamond discs fitted onto the hand-held electrical grinding machine. The speed of Disc rotation must be high (>10000 RPM) and should have a low feed rate (< 1 m/min). It may be required to cool the disc with water. Recommended discs are the thin types generally used for cutting porcelain stoneware. The surface should be kept on a FLAT base while cutting without any gap underneath.

### DRILLING



You can use cutting discs fitted to battery-operated screwdrivers or angle grinders, electrical drills as an alternative.

### INTERNAL CUT / L-SHAPED CUT





To get internal and L-shaped corners & to reduce the risk of breakage, round off the vertex of the internal corner using bits with a radius of at least 5mm. Then cut with diamond discs, be cautious to stop moving the cutting tool forward. To drill and cut using diamond discs, follow the instructions provided above.

#### When using these tools:

- Cool the point being drilled with water
- Don't put too much pressure and bear in mind the resistance of the type of laminated stoneware you are working on
- If you are using tungsten bits, start drilling at a low speed
- If you are using drills or screwdrivers, do not select hammering mode



### EDGE-FINISHING




## MANUALLY TRANSPORTING PORCELAIN FINISH

Only for 1/4" Slabs


### MOVING OUR TILES



### RAISING TILE ONTO A BENCH




✗ INCORRECT




✓ CORRECT

### HANDLING TILES FOR WALL



✗ INCORRECT



✓ CORRECT

## TECHNICAL SPECIFICATIONS

CHARACTERISTIC	STANDARD AS PER ISO-13006/2018 En14411 gr.bla	MOTTO VALUE	TEST METHOD
Regulatory Properties			
Deviation in Length & Width	±0.5%	±0.2%	ISO 10545-2
Deviation in Thickness	±5%	±5%	ISO 10545-2
Straightness of Sides	±0.5%	±0.2%	ISO 10545-2
Rectangularity	±0.5%	±0.2%	ISO 10545-2
Surface Flatness	±0.5%	±0.3%	ISO 10545-2
Colour Difference	ΔE<1.00	ΔE<0.30	ISO 10545-16
Glossiness	As per Mfg.	As Per Mfg.	GlossMeter
Structural Properties			
Water Absorption	≤0.5 %	≤0.3 %	ISO 10545-3
Apparent Density	As Per Mfg.	>2.20 g/cc	ISO 10545-3
Massive Mechanical Properties			
Modulus of Rupture	Min.35N/mm <sup>2</sup>	Min.40N/mm <sup>2</sup>	ISO 10545-4
Breaking Strength	Min. 1300 N	Min. 2000 N	ISO 10545-4
Impact Resistance	As per Mfg.	Min. 0.55	ISO 10545-4
Surface Mechanical Properties			
Surface Abrasion Resistance	As per Mfg.	Min. class 3	ISO 10545-7
Moh's Hardness	As per Mfg.	Min. class 4	BS EN 15771
Thermo Hygrometric Properties			
Frost Resistance	As Per Mfg.	Frost Proof	ISO 10545-12
Thermal Shock Resistance	Min. 10 Cycle	Min. 10 Cycle	ISO 10545-9
Moisture Expansion	Max. 0.6mm/m	Max. 0.02mm/m	ISO 10545-10
Thermal Expansion	Max. 9.0 x 10 <sup>-6</sup>	Max. 6.0x10 <sup>-6</sup>	ISO 10545-8
Chemical Properties			
Chemical Resistance	As Per Mfg.	No Damage	ISO 10545-13
Stain Resistance	Resistant	Resistant	ISO 10545-14
Safety Properties			
Slip Resistance	As per Mfg.	N. A.	DIN 51130
Fire Resistance	As per Mfg.	Fire Proof	N. A.

## CLEANING & MAINTENANCE

Our products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

TYPE OF STAIN	CHEMICAL PRODUCT	EXAMPLE
Grease	Alkaline - Solvent	Detergent
Oil	Solvent	Ammonia, Backing Soda
Ink	Oxidant - Solvent	Alcohol, Liquid Bleach, Nail Paint Remover
Rust	Acid	Hydrochloric Acid, Vinegar, Red Harpic
Lime	Acid	Descaling Reagent, Hydro Chloric Acid
Cement	Acid	Hydro Chloric Acid
Wine	Alkaline	Ammonia, Liquid Bleach
Coffee	Alkaline - Solvent	Ammonia, Liquid Bleach
Rubber	Solvent	Alcohol, Thinner
Plaster	Acid	Hydro Chloric Acid
Candle Wax	Solvent	Alcohol, Thinner
Iodine	Oxidant	Liquid Bleach
Blood	Oxidant	Liquid Bleach
Ice Cream	Alkaline	Liquid Bleach

Note: It is recommended that any kind of stain needs to get clean immediately / as soon as possible.

## PACKING DETAILS

Dimension ( mm )	No. of PC's/Box	Square Feet	Weight ( Approx )
800x1600mm	2 Pcs.	27.55 Sq. Feet	52 Kg.



## MOTTO GROUP

8-A N. H., Sartanpar Road, At. Sartanpar, Ta. Wankaner, Morbi - 363 621, Gujarat, India.

Email: [info@mottogroup.in](mailto:info@mottogroup.in) | [www.mottogroup.in](http://www.mottogroup.in)

Toll Free Number: 1800 123 2124 / +91 95123 80072